




BELUNO

PRODUCT OVERVIEW



Spring Return Motor Driven Diaphragm Metering Pump



Ultra-strong Anticorrosive Multifunctional Check Valve



Check Valve Function: Overcome the leak defect caused by the small pressure difference between gravity check valve system and pump head cavity.

Delivery High Viscosity Liquid: Check valves adopt spring return technology, so the dosing pump can maintain its displacement and linearity better when delivering high viscosity liquid.

Back Pressure Ability: The coefficient of elasticity of elastic part can be properly adjusted according to customer's requirements so that the dosing pump outlet has different back pressure values.

Safety Valve function: The coefficient of elasticity of elastic element can be properly adjusted according to pipeline system pressure to realize the safety valve function needed by the pipeline system.

Anticorrosive ElasticPart: Check valves adopt PTFE elastic components, so as to realize the optimal anticorrosive function.

Up to 3MPa(435psi)

100% PTFE Diaphragm


Excellent Diaphragm Assembly

The diaphragm, which is made of high quality modified PTFE material, and, work together with the matched protection assembly, greatly increase the lift of motor driven diaphragm dosing pump.

The maximum lift is up to 3.0Mpa. Thus some hydraulic diaphragm pumps would be replaced by this pump, thereby saving cost.



Spring Return Quiet and Steady



With damping stroke sliding bar, all motor pumps not only reserve the advantages of traditional spring return dosing pumps including simple structure, low failure rate and easy to maintain, but also overcome their fatal shortcomings including large pipe shock, large mechanical vibration, part damage, poor flow linearity and high noise brought by ineffective eccentric travel.

Lightweight Design

Advanced lightweight structure: For energy saving and emission reduction, the pumps adopt many high specific strength materials and smart structural design, so the pumps have very high power–displacement ratio.



Intelligent Stroke Adjuster

End the Age of Variable Frequency

Remote Control Electric Stroke Adjuster: It can receive analog signal (4–20mA) to change the stroke length of dosing pump in real time, further, accurately modify the displacement of dosing pump. The adjuster overcomes all major defects of modifying the capacity of dosing pump by variable frequency speed control.



Manual Control Electric Stroke Adjuster: The stroke length of dosing pump can be accurately set and displayed via the operation panel of the adjuster. With error compensation function, the adjuster overcomes the error between actual displacement and its set value directly caused by the random change of stroke length of dosing pump, because traditional knob adjuster doesn't have the self-lock function.

Model Code

Code	Example	BLWL	410	0.6	PVT	A	H
Model	BLJS BLJL BLWS BLWL BL1000 BL2000 HND						
Capacity	L/H						
Pressure	MPa						
Dosing Head Material	Pump Head	Diaphragm	Valve Seat	Valve Ball	Seal Ring		
PVT----	PVC	PTFE	PTFE	Ceramic	FKM		
PVDF----	PVDF	PTFE	PTFE	Ceramic	FKM		
SST----	SS316	PTFE	SS316	SS316	FKM		
PTF----	PTFE	PTFE	PTFE	Ceramic	---		
Electric power Supply	A-----	3ph 380V 50Hz/60Hz					
	VF-----	Variable Frequency Motor					
	EX-----	Explosion-proof Motor Exd II BT4					
	B-----	1ph 220v 50Hz/60Hz					
	C-----	Special requirements, otherwise noted					
Control Version	H-----	Manual					
	I-----	Electric stroke adjuster					

*Example

1. Maximum lift is 6kg, Capacity is 370L/h, 380V 50Hz, PVC pump head, 3PH 380V 50Hz, adjustment mode: electric stroke adjustment.

Selected model:

BLWL-410/0.6-PVT-A-I

2. Maximum lift is 6kg, Capacity is 370L/h, 380V 50Hz, PVDF pump head, 3PH 380V 50Hz variable frequency motor adjustment mode: manual.

Selected model:

BLWL-410/0.6-PVDF-AVF-H

BLJ


1. Eccentric shaft is supported by bearings in front and rear and the cantilever shaft structure of the most of manufacturers on the market is abandoned; the speed reducing motor does not bear axial force and only transmits torque, and this extends the service life of speed reducing motor and makes the process more stable.
2. Installation and maintenance are simple and convenient; grease is used for lubrication in the box body and grease is added conveniently, making maintenance easy.
3. Stroke length can be adjusted at will during running.
4. PVC, PVDF, PTFE and SS316 materials pump head are applicable to dose different kinds of chemical liquid.
5. The pure PTFE diaphragm that has a super-long service life guarantees the stability and safety of dosing.
6. It can be directly installed on a dosing barrel and this is economical and convenient.



Technical Specifications

Model	Capacity L/h		Max. Pressure Bar		Stroke Length (mm)	Diaphragm Diameter (mm)	Pump Speed (SPM)		Single-stroke Flow (ml/stroke)	Motor Power (W)
	50hz	60hz	50hz	60hz			50hz	60hz		
BLJS- 40/1.0	40	48	10	8	5	90	87	104	9.7	60
BLJS- 60/0.5	60	72	5	4	5	90	104	125	9.7	60
BLJS- 75/0.5	75	90	5	4	5	90	130	156	9.7	60
BLJS- 100/0.5	100	120	5	4	8	90	104	125	16.5	60
BLJS- 130/0.5	130	156	5	4	8	90	130	156	16.5	60
BLJS- 150/0.3	150	180	3	2.4	5	105	130	156	19.2	60
BLJL- 70/1.0	70	84	10	8	8	90	87	104	13.4	90
BLJL- 80/0.7	80	96	7	5.6	5	90	130	156	10.3	90
BLJL- 105/0.7	105	126	7	5.6	8	90	104	125	16.8	90
BLJL- 150/0.5	150	180	5	4	5	105	130	156	19.2	90

Dimensional Drawing



Pump Head Material and Size

Model	Material	A	B	C	D	E	F	Interface Size	
								Thread Size	Socket Pipe Size
BLJS-40/1.0~130/0.5	PVC	224	29	90	300	130	310	G 1"	G1/2"-DN15
	PVDF	224	29	90	300	130	310	G 1"	G1/2"-DN15
	PTFE	178	6	90	300	130	310	G 1"	/
	SS316	178	6	97	302	130	310	G 1"	/
BLJS-150/0.3	PVC	239	42	90	300	137	310	G 1"	G1/2"-DN15
	PVDF	224	29	90	300	130	310	G 1"	G1/2"-DN15
	PTFE	193	14	90	300	137	310	G 1"	/
	SS316	193	14	97	302	137	310	G 1"	/
BLJL 70/1.0~105/0.7	PVC	224	29	90	300	130	325	G 1"	G1/2"-DN15
	PVDF	224	29	90	300	130	310	G 1"	G1/2"-DN15
	PTFE	178	6	90	300	130	325	G 1"	G1/2"-DN15
	SS316	178	6	97	302	130	325	G 1"	/
BLJL 150/0.5	PVC	239	42	90	300	137	325	G 1"	G1/2"-DN15
	PVDF	224	29	90	300	130	310	G 1"	G1/2"-DN15
	PTFE	193	14	90	300	137	325	G 1"	/
	SS316	193	14	97	302	137	325	G 1"	/

Typical Installation Diagram

